

| Select Patio Door | Size Tested | | | NAFS Ratings | | | |
|----------------------------|---|------------------|--------------------|--|-----------------------|-------------------------|--------------------------------|
| | 6'8" Height - 1815x2025 (71x80) | | | AAMA/WDMA/CSA/I.S.2-/A440-08 R-PG50 | | | |
| | 8' Height - 2135x2433 (84x96) | | | AAMA/WDMA/CSA/I.S.2-/A440-08 &A440S1-09 R-PG35 | | | |
| | OXXO Configuration 3670x2020 (144.4375x79.5) | | | AAMA/WDMA/CSA/I.S.2-/A440-11 &A440S1-17 R-PG30 | | | |
| | High Performance OX-1803x2006 (71x79) | | | AAMA/WDMA/CSA 101/I.S.2-/A440-11 &A440S1-17. R-PG50 | | | |
| Glass Options | Energy Rating | U-value (metric) | U-value (imperial) | Solar Heat Gain Coefficient | Visible Transmittance | Condensation Resistance | Energy Star Zones Oct 23, 2023 |
| Clear | 16 | 2.67 | 0.47 | 0.61 | 0.63 | 44 | - |
| Clear w Grills | 11 | 2.67 | 0.47 | 0.53 | 0.55 | 44 | - |
| LoE/Argon | 31 | 1.82 | 0.32 | 0.55 | 0.61 | 56 | - |
| LoE/Argon w Grills | 27 | 1.82 | 0.32 | 0.48 | 0.54 | 56 | - |
| Energlass | 32 | 1.76 | 0.31 | 0.55 | 0.61 | 58 | - |
| Energlass w Grills | 28 | 1.76 | 0.31 | 0.48 | 0.54 | 58 | - |
| LoE/Argon LSG | 17 | 1.70 | 0.30 | 0.27 | 0.53 | 57 | - |
| LoE/Argon LSG w Grills | 16 | 1.70 | 0.30 | 0.24 | 0.46 | 57 | - |
| Energlass-LSG | 18 | 1.65 | 0.29 | 0.27 | 0.53 | 59 | - |
| Energlass-LSG w Grills | 17 | 1.65 | 0.29 | 0.24 | 0.46 | 59 | - |
| Triple LoE/Argon x1 LSG | 20 | 1.53 | 0.27 | 0.25 | 0.48 | 62 | - |
| Energlass Plus Argon LSG | 25 | 1.25 | 0.22 | 0.23 | 0.40 | 62 | N,NC,SC,S |
| Energlass Plus Krypton LSG | 29 | 1.02 | 0.18 | 0.22 | 0.40 | 62 | N,NC,SC,S |
| Triple LoE/Argon x1 | 32 | 1.59 | 0.28 | 0.49 | 0.56 | 60 | - |
| Energlass Plus Argon | 37 | 1.31 | 0.23 | 0.47 | 0.55 | 62 | - |
| Energlass Plus Krypton | 41 | 1.14 | 0.20 | 0.47 | 0.55 | 62 | - |

| Tilt and Turn Doors | Size Tested | | | NAFS Ratings | | | |
|----------------------------|---------------|------------------|--------------------|-----------------------------|-----------------------|-------------------------|--------------------------------|
| | 40.6" x 95.7" | | | Outswing Door=LC-PG70-SHD | | | |
| | 36" x 83" | | | Inswing Door=LC-PG40-SHD | | | |
| | | | | | | | |
| Glass Options | Energy Rating | U-value (metric) | U-value (imperial) | Solar Heat Gain Coefficient | Visible Transmittance | Condensation Resistance | Energy Star Zones Oct 23, 2023 |
| LoE/Argon | 26 | 1.7 | 0.30 | 0.41 | 0.45 | 61 | - |
| LoE/Argon w Grills | 23 | 1.7 | 0.30 | 0.35 | 0.39 | 61 | - |
| Energlass | 26 | 1.7 | 0.30 | 0.41 | 0.45 | 63 | - |
| Energlass w Grills | 23 | 1.7 | 0.30 | 0.35 | 0.39 | 63 | - |
| LoE/Argon-LSG | 17 | 1.6 | 0.29 | 0.23 | 0.40 | 63 | - |
| LoE/Argon-LSG w Grills | 15 | 1.6 | 0.29 | 0.20 | 0.34 | 63 | - |
| Energlass-LSG | 17 | 1.6 | 0.29 | 0.23 | 0.40 | 65 | - |
| Energlass-LSG w Grills | 15 | 1.6 | 0.29 | 0.20 | 0.34 | 65 | - |
| Triple LoE/Argon x 1 LSG | 21 | 1.4 | 0.25 | 0.21 | 0.36 | 65 | N,NC,SC,S |
| Triple LoE/Argon x 1 LSG-G | 19 | 1.4 | 0.25 | 0.18 | 0.31 | 65 | N,NC,SC,S |
| Energlass Plus Argon LSG | 24 | 1.2 | 0.22 | 0.18 | 0.31 | 65 | N,NC,SC,S |
| Energlass Plus Argon LSG-G | 22 | 1.2 | 0.22 | 0.16 | 0.26 | 65 | N,NC,SC,S |
| Triple LoE/Argon x 1 | 29 | 1.5 | 0.26 | 0.37 | 0.42 | 64 | N,NC |
| Triple LoE/Argon x 1 | 26 | 1.5 | 0.26 | 0.32 | 0.35 | 64 | N,NC |
| Energlass Plus Argon | 33 | 1.2 | 0.22 | 0.36 | 0.41 | 66 | N,NC |
| Energlass Plus Argon-G | 30 | 1.2 | 0.22 | 0.31 | 0.35 | 66 | N,NC |